

V type Spring

● は切っている状態のまま ◐ はその面が平らになっている側

品番		自由長	スプリングレート	線径	ID (upper)	先端形状	ID (lower)	先端形状
V-1	E90 RC	270	7	Φ13.2	Φ60	●	Φ62.5	◐
V-2	E92 RC	220	12	Φ14	Φ60	●	Φ62.5	◐
V-3	KK-0010	200	3.8 & 5.8	Φ11.7	Φ62.5	●	Φ62.5	◐
V-4	KK-0063-A	140	8	Φ10.8	Φ62.5	●	Φ62.5	◐
V-5	KK-0046	180	10.5	Φ13	Φ73	●	Φ62.5	◐
V-6	180-3A	180	3	Φ9.7	Φ80	◐	Φ62.5	◐
V-7	180-5A	180	5	Φ10.7	Φ80	◐	Φ62.5	◐
V-8	KK-0036	190	3.4	Φ12	Φ64	◐	Φ62.5	◐
V-9	KK-0054-A	230	13	Φ14.2	Φ73	●	Φ62.5	◐
V-10	KK-0060-C	180	3	Φ9.2	Φ80	●	Φ62.5	◐
V-11	M5 RC	160	12	Φ13.5	Φ63	●	Φ106	◐
V-12	M3 RC	210	3.9 & 6.6	Φ11.7	Φ83.5	●	Φ62.5	◐
V-13	KK-0004	170	5.4	Φ12	Φ96	●	Φ63	◐
V-14	KK-0053-A	260	12	Φ15.5	Φ97	●	Φ62.5	◐
V-15	KK-0053-1-A	210	6.5	Φ12.5	Φ97	●	Φ62.5	◐
V-16	KK-0064-A	185	8	Φ13	Φ99	●	Φ62.5	◐
V-17	KK-0064-1-A	200	15	Φ15.5	Φ99	●	Φ62.5	◐
V-18	KK-0064-2-A	150	15	Φ14.2	Φ99	●	Φ62.5	◐
V-19	KK-0064-3-A	200	12	Φ14.5	Φ99	●	Φ62.5	◐
V-20	KK-0057-A	180	6	Φ13.3	Φ110.5	◐	Φ62.5	◐
V-21	KK-0056-D	155	10	Φ14.3	Φ113	●	Φ62.5	◐
V-22	KK-0056-1-C	125	14	Φ14.5	Φ113	●	Φ62.5	◐
V-23	KK-0041-B	180	8	Φ14.7	Φ145	●	Φ62.5	◐
V-24	KK-0021-1	200	5.5	Φ12.8	Φ65	●	Φ83	◐
V-25	KK-0051-B	170	6	Φ11.8	Φ65	●	Φ83.5	◐
V-26	KK-0051-1-A	140	6	Φ11.5	Φ65	●	Φ83.5	◐
V-27	KK-0055-A	160	10	Φ13	Φ65	◐	Φ83.5	●
V-28	KK-0043-B	200	7.5	Φ13	Φ74	●	Φ83	◐
V-29	KK-0061-A	135	3	Φ9.5	Φ80	●	Φ83	◐
V-30	KK-0061-B	115	3	Φ9.5	Φ80	●	Φ83	◐
V-31	KK-0061-1-A	110	7	Φ10.8	Φ80	●	Φ83	◐
V-32	KK-0061-2-A	90	7	Φ10.2	Φ80	●	Φ83	◐

V-33	KK-0061-3-A	155	5.5	Φ11.2	Φ80	●	Φ83	◐
V-34	KK-0019-1	190	7	Φ13.3	Φ84.5	●	Φ83.5	◐
V-35	KK-0019-2	200	5.5	Φ12.2	Φ84.5	●	Φ83.5	◐
V-36	KK-0060-B	180	4.7	Φ10.5	Φ80	●	Φ62.5	◐
V-37	KK-0058-A	225	7	Φ13.5	Φ92	●	Φ83.5	◐
V-38	KK-0067-A	220	9.7	Φ16	Φ101	●	Φ100	◐
V-39	KK-0052-A	220	7.5	Φ14.5	Φ77	●	Φ110	◐
V-40	KK-0029	220	7.2	Φ15.5	Φ115	●	Φ110	◐
V-41	KK-0038	190	5	Φ13.5	Φ115	●	Φ110	◐
V-42	KK-0050-A	180	4	Φ11.5	Φ75	●	Φ110.5	◐
V-43	KK-0062-A	190	2.1	Φ11	Φ97	●	Φ110	◐
V-44	KK-0062-B	160	2.1	Φ10.2	Φ97	●	Φ110	◐
V-45	KK-0068-A	150	5	Φ12.5	Φ97	●	Φ110	◐
V-46	TEANA RC	230	7	Φ14.5	Φ100	●	Φ112	◐
V-47	350Z RC	234	9.9	Φ16	Φ100	●	Φ112	◐
V-48	KK-0019-2	200	5.5	Φ12.2	Φ84.5	●	Φ83.5	◐
V-49	KK-0025-3	200	6	Φ14	Φ65	●	Φ110	◐
V-50	KK-0027-A	200	7	Φ13	Φ50	●	Φ83.5	◐
V-51	KK-0035-B	200	6	Φ14	Φ91	●	Φ110	◐
V-52	KK-0049	190	4.6	Φ12.5	Φ83.5	◐	Φ107	●
V-53	KK-0059	180	8	Φ13.2	Φ62.5	◐	Φ111	●
V-54	KK-0070	210	12	Φ17	Φ110	◐	Φ127	●
V-55	KK-0075	170	12	Φ13.5	Φ62.5	◐	Φ73.5	●
V-56	KK-0078	210	11.8	Φ14	Φ62.5	◐	Φ73.5	●
V-57	KK-0085-A	160	4.5	Φ11.2	Φ83	◐	Φ106	●
V-58	KK-0086-A	180	5.5	Φ13	Φ103	●	Φ110	◐
V-59	KK-0088-A	200	5.8	Φ12.2	Φ80.5	●	Φ83	◐
V-60	KK-0090-A	220	5.5	Φ12.8	Φ83.5	◐	Φ100	●
V-61	KK-0094-A	230	14	Φ18	Φ99	●	Φ110	◐
V-62	KK-0079-A	255	14.8	Φ15.5	Φ62.5	◐	Φ70	●
V-63	KK-0092-B	140	3	Φ10.8	Φ91	●	Φ110	◐
V-64	KK-0093-C	180	10	Φ15.5	Φ78	●	Φ90	◐
V-65	KK-0093-1-A	200	14	Φ17	Φ78	●	Φ110	◐
V-66	KK-0097-A	175	6.6	Φ14	Φ62.5	◐	Φ110	◐
V-67	KK-0098-A	230	15	Φ16	Φ62.5	◐	Φ97	●